

Revolutionary Performance with Lasting Quality

Outdoor LED Commercial Lighting Fixtures



- Up to 160 Lumens per Watt Directional
- 100,000+ HRS Rated System
- 7 Year LED Warranty

fixture 6134RLED
finish: Verde Bronze



fixture 99432RLED
finish: Weathered Bronze



*Roof Mounted LED
- 6134 Series shown*

Hanover[®]
LANTERN
Handcrafted in America

OUTDOOR LED COMMERCIAL LIGHTING FIXTURES




5732RLED
H: 25 3/4"
W: 11 1/4"
EPA: 1.02
Fitter: 3" I.D.




99432RLED
H: 28 1/4"
W: 11 1/4"
EPA: 1.02
Fitter: 3" I.D.



5534RLED
H: 31 3/4"
W: 14"
EPA: 1.30
Fitter: 3" I.D.




99634RLED
H: 33 3/4"
W: 13 3/4"
EPA: 1.35
Fitter: 3" I.D.



9434RLED
H: 33 1/4"
W: 13 3/4"
EPA: 1.35
Fitter: 3" I.D.




31832RLED
H: 32 5/8"
W: 14 3/4"
EPA: 1.66
Fitter: 3" I.D.




8432RLED
H: 31"
W: 14 3/4"
EPA: 1.22
Fitter: 3" I.D.



Roof Mounted LED
- 6134 Series shown



30834RLED
H: 42 3/4"
W: 20 3/4"
EPA: 2.60
Fitter: 3" I.D.



6134RLED
H: 38 1/2"
W: 21 1/4"
EPA: 2.60
Fitter: 3" I.D.

Key Benefits

- True white light, large coverage area
- 100,000+ HRS rated system life
- 90% Lumen Maintenance at 100,000+ HRS
- Engineered optics efficiently managed light
- IP66 Wet Location Rate LED Engine
- Superior thermal design (no fans or thermal bandaids)
- Universal 120-277 VAC, 480 VAC optional
- 36kV Surge Suppression
- 7 Year LED Warranty

ORDERING INFORMATION

6134RLED **BLK** **OP** **40** **3000K** **T5M**

1

2

3

4

5

6

1 Model No.

2 Finish
(All finishes available)

3 Panels
(See available options)

4 Wattage
40W, 60W

5 Color Temperature
2200K, 3000K, 4000K, 5000K

6 Light Distribution
T5M = Type 5, T3M = Type 3

To ensure prompt and efficient processing of your order,
Please follow the sequence listed in the example above.
Consult factory for availability.

Hanover
LANTERN
Handcrafted in America

Hanover Lantern
425 East Middle Street
Hanover, PA 17331
Phone: 717-632-6464
Fax: 717-969-2930

www.hanoverlantern.com

HA-SF0220-PDF
Printed in U.S.A.