



- CAST ALUMINUM FINIAL.
- CAST ALUMINUM SQUARE ROOF SECURES TO CAGE W/2 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.
- 4 CLEAR BEVELED GLASS (CBG) CAGE PANELS SECURED W/CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.
- 3 LIGHT CANDLE CLUSTER.
- 3 CANDELABRA SOCKETS WITH PAINTED METAL SLEEVES.
- 2 PC. PAINTED CLUSTER BODY. 25 WATTS MAX. PER SOCKET. (LAMPS NOT SUPPLIED).
- CAST ALUMINUM SQUARE CAGE WITH FROG BOTTOM.
- PAINTED ALUMINUM SLEEVE.
- CAST ALUMINUM BRACKET ARM.
- CAST ALUMINUM KNOB.
- 2 CAST ALUMINUM SCROLLS SECURE TO ROOF WITH (2) 8-32 S.ST'L. SCREWS AND TO WALL WITH (2) #10 S.ST'L. SCREWS AND PLASTIC ANCHOR SHIELDS.

LANTERN IS PREWIRED AND TESTED.
ELECTRICAL COMPONENTS ARE U.L. LISTED.
MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	24 1/4"
WIDTH	36"
PROJECTION	12 3/4"
TOP TO OUTLET	19 1/8"

Drawing for illustration only - scale approximate

	TITLE: "JEFFERSON" 5800 SERIES WALL BRACKET LANTERN W/SCROLLS		
	300 HANOVER LANE HANOVER PA 17231 PH (717) 632-0001 - FAX (717) 632-0002	SCALE: 1=4 DATE: 02/09/05	DWG BY: JEK DWG. NO. B5851