



- CAST ALUMINUM FINIAL.
- CAST ALUMINUM BRACKET ARM.
- PAINTED BRASS SPACER.
- CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.
- PAINTED PIPE NIPPLE.
- 4 CLEAR BEVELED GLASS (CBG) CAGE PANELS SECURE WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.
- 3 LIGHT CANDLE CLUSTER. 3 CANDELABRA SOCKETS W/PAINTED METAL SLEEVES. 2 PC. PAINTED CLUSTER BODY. 25 WATTS MAX. EACH SOCKET (LAMPS NOT SUPPLIED).
- CAST ALUMINUM SQUARE CAGE WITH FROG BOTTOM.
- CAST ALUMINUM KNOB.

LANTERN IS PREWIRED AND TESTED.  
 ELECTRICAL COMPONENTS ARE U.L. LISTED.  
 MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	21 3/4"
WIDTH	9 3/8"
PROJECTION	12 3/4"
TOP TO OUTLET	5 1/4"

Drawing for illustration only — scale approximate

	TITLE: "JEFFERSON" 5800 SERIES WALL BRACKET LANTERN	
	SCALE: 1=4	DATE: 02/09/05