



CAST ALUMINUM 2 PC. FLUTED "S" BRACKET ARM AND WALLPLATE.

CAST ALUMINUM CAP.

CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.

PAINTED PIPE NIPPLE.

4 CLEAR BEVELED GLASS (CBG) CAGE PANELS SECURE WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE—CONTACT FACTORY.

3 LIGHT CANDLE CLUSTER. 3 CANDELABRA SOCKETS W/PAINTED METAL SLEEVES. 2 PC. PAINTED CLUSTER BODY. 25 WATTS MAX. EACH SOCKET (LAMPS NOT SUPPLIED).

CAST ALUMINUM SQUARE CAGE WITH FROG BOTTOM.

CAST ALUMINUM KNOB.

LANTERN IS PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. MOUNTING HARDWARE IS SUPPLIED.

Drawing for illustration only — scale approximate

HEIGHT	20 3/4"
WIDTH	9 3/8"
PROJECTION	14 3/4"
TOP TO OUTLET	10"

	TITLE: "JEFFERSON" 5800 SERIES WALL BRACKET LANTERN		
	SCALE: 1=4	DATE: 02/09/05	DWG BY: JEK