



- CAST ALUMINUM FINIAL.
- CAST ALUMINUM SQUARE ROOF SECURES TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE THUMBSCREWS.
- 4 CLEAR BEVELED GLASS (CBG) CAGE PANELS SECURE WITH CLIPS AND SCREWS. OTHER PANELS AVAILABLE- CONTACT FACTORY.
- 3 LIGHT CANDLE CLUSTER. 3 CANDELABRA SOCKETS W/PAINTED METAL SLEEVES. 2 PC. PAINTED CLUSTER BODY. 25 WATTS MAX. EACH SOCKET (LAMPS NOT SUPPLIED).
- CAST ALUMINUM SQUARE CAGE WITH FROG BOTTOM.
- PAINTED ALUMINUM SLEEVE.
- CAST ALUMINUM CAP.
- CAST ALUMINUM "S" FLUTED BRACKET ARM ATTACHES TO CAST ALUMINUM WALLPLATE W/2 S.ST'L. 1/4-20 BOLTS.

LANTERN IS PREWIRED AND TESTED.
ELECTRICAL COMPONENTS ARE U.L. LISTED.
MOUNTING HARDWARE IS SUPPLIED.

HEIGHT	21"
WIDTH	9 3/8"
PROJECTION	14 3/4"
TOP TO OUTLET	11"

Drawing for illustration only - scale approximate

	TITLE: JEFFERSON™ 5800 SERIES WALL BRACKET LANTERN		
	SCALE: 1=4	DATE: 02/09/05	DWG BY: JEK