

# Revolutionary Performance with Lasting Quality

Outdoor LED Commercial Lighting Fixtures



**fixture 6134FLED**  
*finish: Verde Bronze*




**fixture 99432FLED**  
*finish: Weathered Bronze*

- *Up to 123 Lumens per Watt*
- *50,000+ HRS Rated System*
- *5 Year LED Warranty*




**Hanover**<sup>®</sup>  
LANTERN  
*Handcrafted in America*

# OUTDOOR LED COMMERCIAL LIGHTING FIXTURES



**1640FLED**  
H: 35 1/2"  
W: 14 1/4"  
EPA: 2.00  
Fitter: 3" I.D.



**1630FLED**  
H: 50"  
W: 17 1/2"  
EPA: 2.60  
Fitter: 3" I.D.




**99432FLED**  
H: 28 1/4"  
W: 11 1/4"  
EPA: 1.02  
Fitter: 3" I.D.




**5534FLED**  
H: 31 3/4"  
W: 14"  
EPA: 1.30  
Fitter: 3" I.D.




**99634FLED**  
H: 33 3/4"  
W: 13 3/4"  
EPA: 1.35  
Fitter: 3" I.D.




**9434FLED**  
H: 33 1/4"  
W: 13 3/4"  
EPA: 1.35  
Fitter: 3" I.D.




**31832FLED**  
H: 32 5/8"  
W: 14 3/4"  
EPA: 1.66  
Fitter: 3" I.D.



**8432FLED**  
H: 31"  
W: 14 3/4"  
EPA: 1.22  
Fitter: 3" I.D.



**30834FLED**  
H: 42 3/4"  
W: 20 3/4"  
EPA: 2.60  
Fitter: 3" I.D.



**6134FLED**  
H: 38 1/2"  
W: 21 1/4"  
EPA: 2.60  
Fitter: 3" I.D.



## Key Benefits

- Filamento patent pending post top reflector design results in low uplight and low glare where the optical distribution is tailored for high uniformity and high utilization on the ground.
- High Efficiency 123L/W, 45W
- Hybrid Operation with Magnetic Ballast compatibility  
Type A: Ballasts HPS, MH, MV, Pulse start, Probe start  
Type B: Line voltage 100-277VAC
- Thermal protection dims light to guarantee reliability >65C/150F
- 40C/105FAmbient full light output then gradually dims
- Cold temperature operation to -40C/-40F Compatible
- with enclosed fixtures
- Five years or 50,000 hours warranty\*
- LED Lamp has a IP65 Rating

## ORDERING INFORMATION

**6134FLED** **BLK** **OP** **45** **4000K** **T5M**

1

2

3

4

5

6

1 Model No.

2 Finish  
*(All finishes available)*

3 Panels

4 Wattage  
30W, 45W

5 Color Temperature  
2700K, 3000K, 4000K, 5000K

6 Light Distribution  
T5M = Type 5

**Hanover**  
LANTERN  
*Handcrafted in America*

Hanover Lantern  
425 East Middle Street  
Hanover, PA 17331  
Phone: 717-632-6464  
Fax: 717-969-2930

[www.hanoverlantern.com](http://www.hanoverlantern.com)

To ensure prompt and efficient processing of your order,  
Please follow the sequence listed in the example above.  
*Consult factory for availability.*

HA-SF0922-PDF  
Printed in U.S.A.