



502  
2 AT 180° AS SHOWN

BRACKET ASSEMBLY AS SHOWN ABOVE CONSISTS OF CAST ALUMINUM BRACKET ENDS W/CAST BOTTOM CAPS  
 CAST ALUMINUM CENTER HUB W/ REMOVABLE CAST ALUMINUM CAP, 2" X 1/8" WALL ALUMINUM RECTANGULAR  
 EXTRUDED HORIZONTAL ARMS, WELDED INTERNAL CONSTRUCTION, 11 EA. 5/16-18 S.S.T'L SET SCREWS  
 SUPPLIED FOR SECURING ASSEMBLY TO POST TOP AND SECURING CENTER TOP CAP TO CENTER HUB

\* NOTE: WHEN CENTER MOUNT LANTERN IS SPECIFIED, 1 PC. OF 3" DIA. X .125"  
 WALL X 12" LG. ALUMINUM TUBING SUPPLIED INSTEAD OF TOP CAP. TUBING  
 PROTRUDES OUT OF CENTER HUB 8".



SET SCREW  
 LOCATION TYP.  
 4 SETS 90° AROUND



|               |         |         |     |
|---------------|---------|---------|-----|
| BRACKET ASSY  | 501     | 502     | 503 |
| HEIGHT        | 13 1/2" | 13 1/2" | 21" |
| WIDTH         | 19"     | 34"     | 34" |
| PROJECTION    |         |         |     |
| TOP TO OUTLET |         |         |     |

Drawing for illustration only - scale approximate

425 E. MIDDLE ST. HANOVER PA 17331  
 PH: (717) 632-6464 - FAX: (717) 669-2630

|        |          |         |
|--------|----------|---------|
| SCALE: | DATE:    | DWG BY: |
| 1=4    | 08/28/97 | BLL     |

TITLE:  
 POST TOP  
 ACCESSORY  
 BRACKET ASSEMBLY

DWG. NO.  
 501 THRU 503