



CAST ALUMINUM SQUARE ROOF.

4 OPAL ACRYLIC (OA) CAGE PANELS SECURED BY EXTRUDED LEGS. (OTHER PANELS AVAILABLE—CONTACT FACTORY).

4 EXTRUDED ALUMINUM CAGE LEGS WITH PANEL SLOTS.

PORCELAIN MEDIUM BASE SOCKET. 40 WATTS MAX. (LAMP NOT SUPPLIED).

CAST ALUMINUM BOTTOM CAGE FRAME.

4 3/4"

4 SOCKET TYPE S.ST'L. SET SCREWS SECURE LANTERN TO POST. (TO RELAMP, LOOSEN SET SCREWS AND LIFT ASS'Y OVER LAMP).

4" SQ. X .125" WALL EXTRUDED ALUMINUM POST.

35 1/8"

GROUND LINE

7/8" DIA. WIREWAY HOLE.

CONCRETE FOOTER TO BELOW LOCAL FROST LEVEL OR LOCAL CODE.

18"

10"

LANTERN WILL BE PREWIRED AND TESTED. ALL ELECTRICAL COMPONENTS ARE UL. LISTED. MOUNTING HARDWARE SUPPLIED.

Drawing for illustration only — scale approximate

HEIGHT	35 1/8"
WIDTH	4 3/4"
PROJECTION	
TOP TO OUTLET	

Hanover LANTERN
 425 E. MIDDLE ST. HANOVER, PA 17331
 PH: (717) 632-6464 - FAX: (717) 699-2930

SCALE: 1=4 DATE: 03/02/06 DWG BY: ATV

TITLE: "TERRALIGHT" 6300 SERIES INCANDESCENT GARDEN LANTERN

DWG. NO. 6386