

14 3/4"

37"

8 1/2"

- TURNED ALUMINUM FINIAL.
- CAST ALUMINUM CAP.
- CAST ALUMINUM HEX ROOF SECURES TO CAGE WITH (2) 8-32 BRASS THUMBSCREWS. TO RELAMP, REMOVE BOTH THUMBSCREWS.
- 7 5/8" ACROSS POINTS
- 6 OPAL ACRYLIC (OA) CAGE PANELS SECURE WITH 1 PC. CLEAR POLYCARBONATE U.V. STABILIZED HEX CLIP. (OTHER PANELS AVAILABLE-CONTACT FACTORY).
- WEDGE BASE SOCKET WITH 18 WATT LAMP AND 4 FEET OF #18-2 LOW VOLTAGE CABLE.
- CAST ALUMINUM HEX CAGE WITH FROG BOTTOM.
- 1/4-18 BRASS PIPE NIPPLE.
- CAST ALUMINUM PIPE FITTER WITH (2) 1/4-20 S.ST'L. SET SCREWS TO SECURE FIXTURE TO GARDEN PIPE.
- 1/2" SCHEDULE 40 ALUMINUM PIPE X 24" LG. THREADED ONE END TO ATTACH TO SPIKE.
- 8 1/2" LONG LOW VOLTAGE BLACK ABS FEMALE GROUND SPIKE WITH #8 S.ST'L. SCREW.
- LOW VOLTAGE CABLE CONNECTOR TO BE USED WITH HANOVER LANTERN #10, #12, #14, OR #18 LOW VOLTAGE CABLE.

LANTERN WILL BE PREWIRED AND TESTED. ELECTRICAL COMPONENTS ARE U.L. LISTED. ALL MOUNTING HARDWARE SUPPLIED.  
Drawing for illustration only - scale approximate

HEIGHT	37"
WIDTH	7 5/8"
PROJECTION	
TOP TO OUTLET	



425 E. MIDDLE ST. HANOVER PA 17331  
PH: (717) 632-6464 - FAX: (717) 969-2930

TITLE: TERRALIGHT "JAMESTOWN" LOW VOLTAGE LANTERN

SCALE: 1=4  
DATE: 02/12/20  
DWG BY: JEK

DWG. NO. LVW6315